Specifications



Eaton DT635T

Eaton Cooper Power series T-body, 600A, 35 kV, AC 1 min: 50 kV, DC 15 min: 103 kV, BIL: 150 kV, Min corona: 26 kV, Test point, Cable insul: No cable adapter, No connector, Individual box kit

General specifications	
PRODUCT NAME	Eaton Cooper Power series T-body
CATALOG NUMBER	DT635T
UPC	194006068383
PRODUCT LENGTH/DEPTH	13.5 in
PRODUCT HEIGHT	10.3 in
PRODUCT WIDTH	3.8 in
PRODUCT WEIGHT	3.307 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std 386



Accessories	
WITH TEST POINT	Yes

Additional Specifications	
PACKAGING	Individual box kit
ТҮРЕ	T-body

Conductor	
STRANDED OR COMPRESSED CONDUCTOR SIZE	No connector

Electrical Ratings	
AC 1 MINUTE VOLTAGE WITHSTAND	50 kV
BASIC IMPULSE LEVEL	150 kV
CURRENT RATING	600A
MAXIMUM RATING PHASE-TO-GROUND	21.1 kV
CORONA VOLTAGE LEVEL - MIN	26 kV
STANDARD VOLTAGE CLASS	35 kV

Resources SPECIFICATIONS AND DATASHEETS Eaton Specification Sheet - DT635T Line installation and protective equipment specifiers guide

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland

Eaton.com

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

© 2025 Eaton. All Rights Reserved.

